

FEDERAL OPERATING PERMIT

A FEDERAL OPERATING PERMIT IS HEREBY ISSUED TO

KM Liquids Terminals LLC

AUTHORIZING THE OPERATION OF

Jefferson Street Truck Rack
Special Warehousing and Storage

LOCATED AT

Harris County, Texas

Latitude 29° 43' 0" Longitude 95° 11' 2"

Regulated Entity Number: RN100225986

This permit is issued in accordance with and subject to the Texas Clean Air Act (TCAA), Chapter 382 of the Texas Health and Safety Code and Title 30 Texas Administrative Code Chapter 122 (30 TAC Chapter 122), Federal Operating Permits. Under 30 TAC Chapter 122, this permit constitutes the permit holder's authority to operate the site and emission units listed in this permit. Operations of the site and emission units listed in this permit are subject to all additional rules or amended rules and orders of the Commission pursuant to the TCAA.

This permit does not relieve the permit holder from the responsibility of obtaining New Source Review authorization for new, modified, or existing facilities in accordance with 30 TAC Chapter 116, Control of Air Pollution by Permits for New Construction or Modification.

The site and emission units authorized by this permit shall be operated in accordance with 30 TAC Chapter 122, the general terms and conditions, special terms and conditions, and attachments contained herein.

This permit shall expire five years from the date of issuance. The renewal requirements specified in 30 TAC § 122.241 must be satisfied in order to renew the authorization to operate the site and emission units.

Permit No: O993 Issuance Date: September 26, 2011

For the Commission

Table of Contents

Section	Page
General Terms and Conditions	1
Special Terms and Conditions	1
Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting	1
Additional Monitoring Requirements	11
New Source Review Authorization Requirements	12
Compliance Requirements.....	13
Risk Management Plan	15
Permit Location.....	15
Attachments	16
Applicable Requirements Summary	17
Additional Monitoring Requirements	31
New Source Review Authorization References.....	35
Appendix A	39
Acronym List	40

General Terms and Conditions

The permit holder shall comply with all terms and conditions contained in 30 TAC § 122.143 (General Terms and Conditions), 30 TAC § 122.144 (Recordkeeping Terms and Conditions), 30 TAC § 122.145 (Reporting Terms and Conditions), and 30 TAC § 122.146 (Compliance Certification Terms and Conditions).

In accordance with 30 TAC § 122.144(1), records of required monitoring data and support information required by this permit, or any applicable requirement codified in this permit, are required to be maintained for a period of five years from the date of the monitoring report, sample, or application unless a longer data retention period is specified in an applicable requirement. The five year record retention period supersedes any less stringent retention requirement that may be specified in a condition of a permit identified in the New Source Review Authorization attachment.

If the permit holder chooses to demonstrate that this permit is no longer required, a written request to void this permit shall be submitted to the Texas Commission on Environmental Quality (TCEQ) by the Responsible Official in accordance with 30 TAC § 122.161(e). The permit holder shall comply with the permit's requirements, including compliance certification and deviation reporting, until notified by the TCEQ that this permit is voided.

The permit holder shall comply with 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit.

All reports required by this permit must include in the submittal a cover letter which identifies the following information: company name, TCEQ regulated entity number, air account number (if assigned), site name, area name (if applicable), and Air Permits Division permit number(s).

Special Terms and Conditions: Emission Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

1. Permit holder shall comply with the following requirements:
 - A. Emission units (including groups and processes) in the Applicable Requirements Summary attachment shall meet the limitations, standards, equipment specifications, monitoring, recordkeeping, reporting, testing, and other requirements listed in the Applicable Requirements Summary attachment to assure compliance with the permit.
 - B. The textual description in the column titled "Textual Description" in the Applicable Requirements Summary attachment is not enforceable and is not deemed as a substitute for the actual regulatory language. The Textual Description is provided for information purposes only.

- C. A citation listed on the Applicable Requirements Summary attachment, which has a notation [G] listed before it, shall include the referenced section and subsection for all commission rules, or paragraphs for all federal and state regulations and all subordinate paragraphs, subparagraphs and clauses, subclauses, and items contained within the referenced citation as applicable requirements.
 - D. When a grouped citation, notated with a [G] in the Applicable Requirements Summary, contains multiple compliance options, the permit holder must keep records of when each compliance option was used.
 - E. Emission units subject to 40 CFR Part 63, Subpart BBBBBB as identified in the attached Applicable Requirements Summary table are subject to 30 TAC Chapter 113, Subchapter C, § 113.1370 which incorporates the 40 CFR Part 63 Subpart by reference.
2. The permit holder shall comply with the following sections of 30 TAC Chapter 101 (General Air Quality Rules):
- A. Title 30 TAC § 101.1 (relating to Definitions), insofar as the terms defined in this section are used to define the terms used in other applicable requirements
 - B. Title 30 TAC § 101.3 (relating to Circumvention)
 - C. Title 30 TAC § 101.8 (relating to Sampling), if such action has been requested by the TCEQ
 - D. Title 30 TAC § 101.9 (relating to Sampling Ports), if such action has been requested by the TCEQ
 - E. Title 30 TAC § 101.10 (relating to Emissions Inventory Requirements)
 - F. Title 30 TAC § 101.201 (relating to Emission Event Reporting and Recordkeeping Requirements)
 - G. Title 30 TAC § 101.211 (relating to Scheduled Maintenance, Start-up, and Shutdown Reporting and Recordkeeping Requirements)
 - H. Title 30 TAC § 101.221 (relating to Operational Requirements)
 - I. Title 30 TAC § 101.222 (relating to Demonstrations)
 - J. Title 30 TAC § 101.223 (relating to Actions to Reduce Excessive Emissions)
3. Permit holder shall comply with the following requirements of 30 TAC Chapter 111:

- A. Visible emissions from stationary vents with a flow rate of less than 100,000 actual cubic feet per minute and constructed after January 31, 1972 that are not listed in the Applicable Requirements Summary attachment for 30 TAC Chapter 111, Subchapter A, Division 1 , shall not exceed 20% opacity averaged over a six-minute period. The permit holder shall comply with the following requirements for stationary vents at the site subject to this standard:
- (i) Title 30 TAC § 111.111(a)(1)(B) (relating to Requirements for Specified Sources)
 - (ii) Title 30 TAC § 111.111(a)(1)(E)
 - (iii) Title 30 TAC § 111.111(a)(1)(F)(i), (ii), (iii), or (iv)
 - (iv) For emission units with vent emissions subject to 30 TAC § 111.111(a)(1)(B), complying with 30 TAC § 111.111(a)(1)(F)(ii), (iii), or (iv), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146. These periodic monitoring requirements do not apply to vents that are not capable of producing visible emissions such as vents that emit only colorless VOCs; vents from non-fuming liquids; vents that provide passive ventilation, such as plumbing vents; or vent emissions from any other source that does not obstruct the transmission of light. Vents, as specified in the “Applicable Requirements Summary” attachment, that are subject to the emission limitation of 30 TAC § 111.111(a)(1)(B) are not subject to the following periodic monitoring requirements:
 - (1) An observation of stationary vents from emission units in operation shall be conducted at least once during each calendar quarter unless the emission unit is not operating for the entire quarter.
 - (2) For stationary vents from a combustion source, if an alternative to the normally fired fuel is fired for a period greater than or equal to 24 consecutive hours, the permit holder shall conduct an observation of the stationary vent for each such period to determine if visible emissions are present. If such period is greater than 3 months, observations shall be conducted once during each quarter. Supplementing the normally fired fuel with natural gas or fuel gas to increase the net heating value to the minimum required value does not constitute creation of an alternative fuel.

- (3) Records of all observations shall be maintained.
- (4) Visible emissions observations of emission units operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of emission units operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions observations shall be made during times when the activities described in 30 TAC § 111.111(a)(1)(E) are not taking place. Visible emissions shall be determined with each stationary vent in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each stationary vent during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.
- (5) Compliance Certification:
 - (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(1) and (a)(1)(B).
 - (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(1)(F) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation

on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader.

- (c) Some vents may be subject to multiple visible emission or monitoring requirements. All credible data must be considered when certifying compliance with this requirement even if the observation or monitoring was performed to demonstrate compliance with a different requirement.

B. For visible emissions from a building, enclosed facility, or other structure; the permit holder shall comply with the following requirements:

- (i) Title 30 TAC § 111.111(a)(7)(A) (relating to Requirements for Specified Sources)
- (ii) Title 30 TAC § 111.111(a)(7)(B)(i) or (ii)
- (iii) For a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source subject to 30 TAC § 111.111(a)(7)(A), complying with 30 TAC § 111.111(a)(7)(B)(i) or (ii), and capable of producing visible emissions from, but not limited to, particulate matter, acid gases and NO_x, the permit holder shall also comply with the following periodic monitoring requirements for the purpose of annual compliance certification under 30 TAC § 122.146:
 - (1) An observation of visible emissions from a building containing an air emission source, enclosed facility, or other structure containing or associated with an air emission source which is required to comply with 30 TAC § 111.111(a)(7)(A) shall be conducted at least once during each calendar quarter unless the air emission source or enclosed facility is not operating for the entire quarter.
 - (2) Records of all observations shall be maintained.
 - (3) Visible emissions observations of air emission sources or enclosed facilities operated during daylight hours shall be conducted no earlier than one hour after sunrise and no later than one hour before sunset. Visible emissions observations of air emission sources or enclosed facilities operated only at night must be made with additional lighting and the temporary installation of contrasting backgrounds. Visible emissions shall be determined with each emissions outlet in clear view of the observer. The observer shall be at least 15 feet, but not more than 0.25 mile, away from each emissions

outlet during the observation. For outdoor locations, the observer shall select a position where the sun is not directly in the observer's eyes. When condensed water vapor is present within the plume, as it emerges from the emissions outlet, observations must be made beyond the point in the plume at which condensed water vapor is no longer visible. When water vapor within the plume condenses and becomes visible at a distance from the emissions outlet, the observation shall be evaluated at the outlet prior to condensation of water vapor. A certified opacity reader is not required for visible emissions observations.

(4) Compliance Certification:

- (a) If visible emissions are not present during the observation, the RO may certify that the source is in compliance with the applicable opacity requirement in 30 TAC § 111.111(a)(7) and (a)(7)(A)
- (b) However, if visible emissions are present during the observation, the permit holder shall either list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2) or conduct the appropriate opacity test specified in 30 TAC § 111.111(a)(7)(B) as soon as practicable, but no later than 24 hours after observing visible emissions to determine if the source is in compliance with the opacity requirements. If an opacity test is performed and the source is determined to be in compliance, the RO may certify that the source is in compliance with the applicable opacity requirement. However, if an opacity test is performed and the source is determined to be out of compliance, the permit holder shall list this occurrence as a deviation on the next deviation report as required under 30 TAC § 122.145(2). The opacity test must be performed by a certified opacity reader

C. Permit holders for sites that have materials handling, construction, roads, streets, alleys, and parking lots shall comply with the following requirements:

- (i) Title 30 TAC § 111.143 (relating to Materials Handling)
- (ii) Title 30 TAC § 111.145 (relating to Construction and Demolition)
- (iii) Title 30 TAC § 111.147 (relating to Roads, Streets, and Alleys)

- (iv) Title 30 TAC § 111.149 (relating to Parking Lots)
- D. Emission limits on nonagricultural processes, except for the steam generators specified in 30 TAC § 111.153, shall comply with the following requirements:
 - (i) Emissions of PM from any source may not exceed the allowable rates as required in 30 TAC § 111.151(a) (relating to Allowable Emissions Limits)
 - (ii) Sources with an effective stack height (h_e) less than the standard effective stack height (H_e), must reduce the allowable emission level by multiplying it by $[h_e/H_e]^2$ as required in 30 TAC § 111.151(b)
 - (iii) Effective stack height shall be calculated by the equation specified in 30 TAC § 111.151(c)
- 4. The permit holder shall comply with the following requirements of 30 TAC Chapter 115, Subchapter F, Division 3, Degassing of Storage Tanks, Transport Vessels and Marine Vessels:
 - A. For degassing of stationary VOC storage tanks, the permit holder shall comply with the following requirements:
 - (i) Title 30 TAC § 115.541(a) - (c) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.541(f) (relating to Emission Specifications), for floating roof storage tanks
 - (iii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iv) Title 30 TAC § 115.542(b) - (d), (relating to Control Requirements)
 - (v) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)
 - (vi) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
 - (vii) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
 - (viii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices

- (ix) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
 - (x) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
 - (xi) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
 - (xii) Title 30 TAC § 115.545(1) - (7), (9) - (11) and (13) (relating to Approved Test Methods)
 - (xiii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
 - (xiv) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
 - (xv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
 - (xvi) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification
 - (xvii) Title 30 TAC § 115.547(4) (relating to Exemptions)
- B. For the degassing of all transport vessels with a nominal capacity of 8,000 gallons or more, the permit holder shall comply with the following requirements:
- (i) Title 30 TAC § 115.541(a) - (c) and (d) (relating to Emission Specifications)
 - (ii) Title 30 TAC § 115.542(a) and (a)(1), (a)(2), (a)(3) or (a)(4) (relating to Control Requirements). Where the requirements of 30 TAC Chapter 115, Subchapter F contain multiple compliance options, the permit holder shall keep records of when each compliance option was used.
 - (iii) Title 30 TAC § 115.542(b), (c) and (e) (relating to Control Requirements)
 - (iv) Title 30 TAC § 115.543 (relating to Alternate Control Requirements)

- (v) Title 30 TAC § 115.544(a)(1) and (a)(2) (relating to Inspection, Monitoring, and Testing Requirements), for inspections
- (vi) Title 30 TAC § 115.544(b) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring
- (vii) Title 30 TAC § 115.544(b)(1) and (b)(2) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring of control devices
- (viii) Title 30 TAC § 115.544(b)(2)(A) - (J) (relating to Inspection, Monitoring, and Testing Requirements), for monitoring (as appropriate to the control device)
- (ix) Title 30 TAC § 115.544(b)(3), (b)(4) and (b)(6) (relating to Inspection, Monitoring, and Testing Requirements), for VOC concentration or lower explosive limit threshold monitoring
- (x) Title 30 TAC § 115.544(c), and (c)(1) - (c)(3) (relating to Inspection, Monitoring, and Testing Requirements), for testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xi) Title 30 TAC § 115.545(1) - (11) and (13) (relating to Approved Test Methods)
- (xii) Title 30 TAC § 115.546(a), (a)(1) and (a)(3) (relating to Recordkeeping and Notification Requirements), for recordkeeping
- (xiii) Title 30 TAC § 115.546(a)(2) and (a)(2)(A) - (J) (relating to Recordkeeping and Notification Requirements), for recordkeeping (as appropriate to the control device)
- (xiv) Title 30 TAC § 115.546(a)(4) (relating to Recordkeeping and Notification Requirements), for recordkeeping of testing of control devices used to comply with 30 TAC § 115.542(a)(1)
- (xv) Title 30 TAC § 115.546(b) (relating to Recordkeeping and Notification Requirements), for notification

5. The permit holder shall comply with the following requirements of 30 TAC Chapter 117:

- A. For boilers, process heaters, and stationary reciprocating engines exempt from Subchapter D, Division 1 at minor sources of NO_x under 30 TAC § 117.2003(a), the permit holder shall comply with 30 TAC §§ 117.2030(c), 117.2035(g), 117.2045(b) and 117.2045(c).

6. The permit holder shall comply with the following requirements for units subject to any subpart of 40 CFR Part 60, unless otherwise stated in the applicable subpart:
 - A. Title 40 CFR § 60.7 (relating to Notification and Recordkeeping)
 - B. Title 40 CFR § 60.8 (relating to Performance Tests)
 - C. Title 40 CFR § 60.11 (relating to Compliance with Standards and Maintenance Requirements)
 - D. Title 40 CFR § 60.12 (relating to Circumvention)
 - E. Title 40 CFR § 60.13 (relating to Monitoring Requirements)
 - F. Title 40 CFR § 60.14 (relating to Modification)
 - G. Title 40 CFR § 60.15 (relating to Reconstruction)
 - H. Title 40 CFR § 60.19 (relating to General Notification and Reporting Requirements)
7. For the bulk gasoline terminals specified in 40 CFR Part 60, Subpart XX, the permit holder shall comply with the following requirements:
 - A. Title 40 CFR § 60.502(e) - (f) (relating to Standard for VOC Emissions from Bulk Gasoline Terminals)
 - B. Title 40 CFR § 60.505(a) - (b), and (d) (relating to Reporting and Recordkeeping)
8. The permit holder shall comply with the requirements of 30 TAC Chapter 113, Subchapter C, § 113.100 for units subject to any subpart of 40 CFR Part 63, unless otherwise stated in the applicable subpart.
9. For the bulk gasoline terminals specified in 40 CFR Part 63, Subpart R, the permit holder shall comply with 40 CFR § 63.420(a)(2) (Title 30 TAC Chapter 113, Subchapter C, § 113.230 incorporated by reference).
10. For each bulk gasoline terminal specified in 40 CFR Part 63, Subpart BBBBBB, the permit holder shall comply with the following requirements (Title 30 TAC, Subchapter C, § 113.1370 incorporated by reference):
 - A. Title 40 CFR § 60.502(e) - (f), as required by Title 40 CFR § 63.11088(a)
 - B. Title 40 CFR § 63.11085(a), for operation and maintenance of the affected source
 - C. Title 40 CFR § 63.11089(a), for leak inspections at the facility

- D. Title 40 CFR § 63.11089(b) and (c), for log book maintenance and recordkeeping
 - E. Title 40 CFR § 63.11089(d), for delay of repair
 - F. Title 40 CFR § 63.11092(f) and (f)(1), for annual certification of gasoline cargo tanks
 - G. Title 40 CFR § 63.11093(a), for Initial Notification
 - H. Title 40 CFR § 63.11093(b), for Notification of Compliance Status
 - I. Title 40 CFR § 63.11094(d), for recordkeeping
 - J. Title 40 CFR § 63.11094(e), for recordkeeping
 - K. Title 40 CFR § 63.11094(g), for recordkeeping
 - L. Title 40 CFR § 63.11095(a), (a)(3), (b), (b)(5) and (d), for reporting
11. The permit holder shall comply with certified registrations submitted to the TCEQ for purposes of establishing federally enforceable emission limits. A copy of the certified registration shall be maintained with the permit. Records sufficient to demonstrate compliance with the established limits shall be maintained. The certified registration and records demonstrating compliance shall be provided, on request, to representatives of the appropriate TCEQ regional office and any local air pollution control agency having jurisdiction over the site. The permit holder shall submit updated certified registrations when changes at the site require establishment of new emission limits. If changes result in emissions that do not remain below major source thresholds, the permit holder shall submit a revision application to codify the appropriate requirements in the permit.

Additional Monitoring Requirements

12. Unless otherwise specified, the permit holder shall comply with the compliance assurance monitoring requirements as specified in the attached “CAM Summary” upon issuance of the permit. In addition, the permit holder shall comply with the following:
- A. The permit holder shall comply with the terms and conditions contained in 30 TAC § 122.147 (General Terms and Conditions for Compliance Assurance Monitoring).
 - B. The permit holder shall report, consistent with the averaging time identified in the “CAM Summary,” deviations as defined by the deviation limit in the “CAM Summary.” Any monitoring data below a minimum limit or above a maximum limit, that is collected in accordance with the requirements specified in 40 CFR § 64.7(c), shall be reported as a

deviation. Deviations shall be reported according to 30 TAC § 122.145 (Reporting Terms and Conditions).

- C. The permit holder may elect to collect monitoring data on a more frequent basis and average the data, consistent with the averaging time specified in the “CAM Summary,” for purposes of determining whether a deviation has occurred. However, the additional data points must be collected on a regular basis. In no event shall data be collected and used in particular instances in order to avoid reporting deviations. All monitoring data shall be collected in accordance with the requirements specified in 40 CFR § 64.7(c).
- D. The permit holder shall operate the monitoring, identified in the attached “CAM Summary,” in accordance with the provisions of 40 CFR § 64.7.
- E. The permit holder shall comply with the requirements of 40 CFR § 70.6(a)(3)(ii)(A) and 30 TAC § 122.144(1)(A)-(F) for documentation of all required inspections.

New Source Review Authorization Requirements

- 13. Permit holder shall comply with the requirements of New Source Review authorizations issued or claimed by the permit holder for the permitted area, including permits, permits by rule, standard permits, flexible permits, special permits, permits for existing facilities including Voluntary Emissions Reduction Permits and Electric Generating Facility Permits issued under 30 TAC Chapter 116, Subchapter I, or special exemptions referenced in the New Source Review Authorization References attachment. These requirements:
 - A. Are incorporated by reference into this permit as applicable requirements
 - B. Shall be located with this operating permit
 - C. Are not eligible for a permit shield
- 14. The permit holder shall comply with the general requirements of 30 TAC Chapter 106, Subchapter A or the general requirements, if any, in effect at the time of the claim of any PBR.
- 15. The permit holder shall maintain records to demonstrate compliance with any emission limitation or standard that is specified in a permit by rule (PBR) or Standard Permit listed in the New Source Review Authorizations attachment. The records shall yield reliable data from the relevant time period that are representative of the emission unit’s compliance with the PBR or Standard Permit. These records may include, but are not limited to, production capacity and throughput, hours of operation, material safety data sheets (MSDS), chemical composition of raw materials, speciation of air contaminant data, engineering calculations, maintenance records, fugitive data, performance tests,

capture/control device efficiencies, direct pollutant monitoring (CEMS, COMS, or PEMS), or control device parametric monitoring. These records shall be made readily accessible and available as required by 30 TAC § 122.144. Any monitoring or recordkeeping data indicating noncompliance with the PBR or Standard Permit shall be considered and reported as a deviation according to 30 TAC § 122.145 (Reporting Terms and Conditions).

16. The permit holder shall comply with the following requirements for Air Quality Standard Permits:
 - A. Registration requirements listed in 30 TAC § 116.611, unless otherwise provided for in an Air Quality Standard Permit
 - B. General Conditions listed in 30 TAC § 116.615, unless otherwise provided for in an Air Quality Standard Permit
 - C. Applicable requirements of 30 TAC § 116.617 for Pollution Control Projects based on the information contained in the registration application.

Compliance Requirements

17. The permit holder shall certify compliance in accordance with 30 TAC § 122.146. The permit holder shall comply with 30 TAC § 122.146 using at a minimum, but not limited to, the continuous or intermittent compliance method data from monitoring, recordkeeping, reporting, or testing required by the permit and any other credible evidence or information. The certification period may not exceed 12 months and the certification must be submitted within 30 days after the end of the period being certified.
18. Use of Emission Credits to comply with applicable requirements:
 - A. Unless otherwise prohibited, the permit holder may use emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) Offsets for Title 30 TAC Chapter 116
 - B. The permit holder shall comply with the following requirements in order to use the emission credits to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.306(c)(2)

- (ii) The emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 1
- (iii) The executive director has approved the use of the credit according to 30 TAC § 101.306(c)(2)
- (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.302(g) and 30 TAC Chapter 122
- (v) Title 30 TAC § 101.305 (relating to Emission Reductions Achieved Outside the United States)

19. Use of Discrete Emission Credits to comply with the applicable requirements:

- A. Unless otherwise prohibited, the permit holder may use discrete emission credits to comply with the following applicable requirements listed elsewhere in this permit:
 - (i) Title 30 TAC Chapter 115
 - (ii) Title 30 TAC Chapter 117
 - (iii) If applicable, offsets for Title 30 TAC Chapter 116
 - (iv) Temporarily exceed state NSR permit allowables
- B. The permit holder shall comply with the following requirements in order to use the credit to comply with the applicable requirements:
 - (i) The permit holder must notify the TCEQ according to 30 TAC § 101.376(d)
 - (ii) The discrete emission credits to be used must meet all the geographic, timeliness, applicable pollutant type, and availability requirements listed in 30 TAC Chapter 101, Subchapter H, Division 4
 - (iii) The executive director has approved the use of the discrete emission credits according to 30 TAC § 101.376(d)(1)(A)
 - (iv) The permit holder keeps records of the use of credits towards compliance with the applicable requirements in accordance with 30 TAC § 101.372(h) and 30 TAC Chapter 122
 - (v) Title 30 TAC § 101.375 (relating to Emission Reductions Achieved Outside the United States)

Risk Management Plan

20. For processes subject to 40 CFR Part 68 and specified in 40 CFR § 68.10, the permit holder shall comply with the requirements of the Accidental Release Prevention Provisions in 40 CFR Part 68. The permit holder shall submit to the appropriate agency either a compliance schedule for meeting the requirements of 40 CFR Part 68 by the date provided in 40 CFR § 68.10(a), or as part of the compliance certification submitted under this permit, a certification statement that the source is in compliance with all requirements of 40 CFR Part 68, including the registration and submission of a risk management plan.

Permit Location

21. The permit holder shall maintain a copy of this permit and records related to requirements listed in this permit on site.

Attachments

Applicable Requirements Summary

Additional Monitoring Requirements

New Source Review Authorization References

Applicable Requirements Summary

Unit Summary	18
---------------------------	-----------

Applicable Requirements Summary	22
--	-----------

Note: A “none” entry may be noted for some emission sources in this permit’s “Applicable Requirements Summary” under the heading of “Monitoring and Testing Requirements” and/or “Recordkeeping Requirements” and/or “Reporting Requirements.” Such a notation indicates that there are no requirements for the indicated emission source as identified under the respective column heading(s) for the stated portion of the regulation when the emission source is operating under the conditions of the specified SOP Index Number. However, other relevant requirements pursuant to 30 TAC Chapter 122 including Recordkeeping Terms and Conditions (30 TAC § 122.144), Reporting Terms and Conditions (30 TAC § 122.145), and Compliance Certification Terms and Conditions (30 TAC § 122.146) continue to apply.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
A-4	STORAGE TANKS/VESSELS	N/A	R5112-A4	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
FUGITIVES	FUGITIVE EMISSION UNITS	N/A	63BBBBBB-1	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
GRPJFo1	STORAGE TANKS/VESSELS	T35-1, T35-2, T35- 3, T80-1, T80-2, T80-3	REG5-0001	30 TAC Chapter 115, Storage of VOCs	TRUE VAPOR PRESSURE = True vapor pressure is less than 1.0 psia
GRPJFo1	STORAGE TANKS/VESSELS	T35-1, T35-2, T35- 3, T80-1, T80-2, T80-3	REG5-0002	30 TAC Chapter 115, Storage of VOCs	TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPJFo1	STORAGE TANKS/VESSELS	T35-1, T35-2, T35- 3, T80-1, T80-2, T80-3	REG5-0003	30 TAC Chapter 115, Storage of VOCs	TRUE VAPOR PRESSURE = True vapor pressure is greater than or equal to 1.5 psia
GRPJFo1	STORAGE TANKS/VESSELS	T35-1, T35-2, T35- 3, T80-1, T80-2, T80-3	60Ka-0002	40 CFR Part 60, Subpart Ka	No changing attributes.
GRPJFo1	STORAGE TANKS/VESSELS	T35-1, T35-2, T35- 3, T80-1, T80-2, T80-3	63BBBBBB-1	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
GRPJFo2	LOADING/ UNLOADING OPERATIONS	BAY 1, BAY 2, BAY 3, BAY 4, BAY 5, BAY 6, BAY 7, BAY 8, BAY 9	REG5-0001	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure greater than or equal to 0.5 psia.
GRPJFo2	LOADING/ UNLOADING OPERATIONS	BAY 1, BAY 2, BAY 3, BAY 4, BAY 5, BAY 6, BAY 7, BAY	REG5-0003	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Gasoline, True Vapor Pressure = True vapor pressure greater than or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
		8, BAY 9			equal to 0.5 psia.
GRPJFo2	LOADING/ UNLOADING OPERATIONS	BAY 1, BAY 2, BAY 3, BAY 4, BAY 5, BAY 6, BAY 7, BAY 8, BAY 9	REG5-0005	30 TAC Chapter 115, Loading and Unloading of VOC	Product Transferred = Volatile organic compounds other than liquefied petroleum gas and gasoline., True Vapor Pressure = True vapor pressure less than 0.5 psia.
GRPJFo2	LOADING/ UNLOADING OPERATIONS	BAY 1, BAY 2, BAY 3, BAY 4, BAY 5, BAY 6, BAY 7, BAY 8, BAY 9	60XX-0001	40 CFR Part 60, Subpart XX	No changing attributes.
GRPJFo2	LOADING/ UNLOADING OPERATIONS	BAY 1, BAY 2, BAY 3, BAY 4, BAY 5, BAY 6, BAY 7, BAY 8, BAY 9	63BBBBBB-1	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	R5112-01	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is less than 1.0 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	R5112-02	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.0 psia but less than 1.5 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	R5112-03	30 TAC Chapter 115, Storage of VOCs	True Vapor Pressure = True vapor pressure is greater than or equal to 1.5 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	60Kb-2	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
					condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	60Kb-3	40 CFR Part 60, Subpart Kb	Product Stored = Petroleum liquid (other than petroleum or condensate), Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	60Kb-5	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.5 psia but less than 0.75 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	60Kb-6	40 CFR Part 60, Subpart Kb	Product Stored = Volatile organic liquid, Maximum True Vapor Pressure = True vapor pressure is greater than or equal to 0.75 psia but less than 11.1 psia
GRPJFo4	STORAGE TANKS/VESSELS	T10-13, T35-4, T50-4, T80-5	63BBBBBB-1	40 CFR Part 63, Subpart BBBBBB	No changing attributes.
T30-4	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
T80-4	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Unit Summary

Unit/Group/ Process ID No.	Unit Type	Group/Inclusive Units	SOP Index No.	Regulation	Requirement Driver
TK71001	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK71002	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK71003	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TK71004	STORAGE TANKS/VESSELS	N/A	R5112-1	30 TAC Chapter 115, Storage of VOCs	No changing attributes.
TR SUMP-1	STORAGE TANKS/VESSELS	N/A	TAC115-SUMP	30 TAC Chapter 115, Storage of VOCs	No changing attributes.

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
A-4	EU	R5112-A4	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
FUGITIVES	EU	63BBBBBB-1	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	[G]§ 63.11089 The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart BBBBBB
GRPJFo1	EU	REG5-0001	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None
GRPJFo1	EU	REG5-0002	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).			
GRPJFo1	EU	REG5-0003	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(d)(1) § 115.112(d)(2) § 115.112(d)(2)(A) § 115.112(d)(2)(B) § 115.112(d)(2)(C) § 115.112(d)(2)(D) § 115.112(d)(2)(E) [G]§ 115.112(d)(2)(H)	No person shall place, store, or hold in any stationary tank, reservoir, or other container any VOC unless such container is capable of maintaining working pressure sufficient at all times to prevent any vapor or gas loss to the atmosphere, or is equipped with at least the control device specified in either Table I(a) of subsection (a)(1) of this section for VOC other than crude oil and condensate, or Table II(a) of subsection (a)(1) of this section for crude oil and condensate.	§ 115.114(a)(1) [G]§ 115.115(a) § 115.116(a)(4) § 115.116(a)(5)	§ 115.116(a)(2) § 115.116(a)(4) § 115.116(a)(5)	§ 115.114(a)(1)
GRPJFo1	EU	60Ka-0002	VOC	40 CFR Part 60, Subpart Ka	§ 60.112a(a)(2)	Vessels storing petroleum liquids with a TVP > 10.3 kPa (1.5 psia) but < 76.6	§ 60.115a(a) § 60.115a(b)	§ 60.115a(a)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						kPa (11.1 psia) shall have a fixed roof and an internal floating cover with the specified closure device and vents.			
GRPJF01	EU	63BBBBBB-1	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart BBBBBB
GRPJF02	EU	REG5-0001	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.211(1) § 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	Gasoline terminals, in the covered non-attainment counties, shall ensure that VOC emissions do not exceed 0.09 lb/1,000 gal (10.8 mg/liter) of gasoline loaded into transport vessels.	§ 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(4)(C) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216 § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	None
GRPJF02	EU	REG5-0003	VOC	30 TAC Chapter	§ 115.211(1)	Gasoline terminals, in the	§ 115.212(a)(3)(B)	§ 115.216	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
				115, Loading and Unloading of VOC	§ 115.212(a)(2) § 115.212(a)(3)(A) § 115.212(a)(3)(A)(i) § 115.212(a)(3)(B) [G]§ 115.212(a)(3)(C) § 115.212(a)(3)(D) § 115.212(a)(3)(E) § 115.212(a)(4)(A) § 115.212(a)(4)(B) § 115.212(a)(4)(C) § 115.214(a)(1)(B) § 115.214(a)(1)(C)	covered non-attainment counties, shall ensure that VOC emissions do not exceed 0.09 lb/1,000 gal (10.8 mg/liter) of gasoline loaded into transport vessels.	[G]§ 115.212(a)(3)(C) § 115.212(a)(4)(C) § 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.214(a)(1)(A)(ii) § 115.214(a)(1)(A)(iii) § 115.214(a)(2) § 115.215 § 115.215(1) § 115.215(10) [G]§ 115.215(2) § 115.215(4) § 115.215(5) § 115.215(6) § 115.215(9) § 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) ** See CAM Summary	§ 115.216(1) § 115.216(1)(A) § 115.216(1)(A)(iv) § 115.216(2) § 115.216(3)(A) § 115.216(3)(A)(i) § 115.216(3)(A)(ii) § 115.216(3)(A)(iii) § 115.216(3)(B) [G]§ 115.216(3)(E)	
GRPJFo2	EU	REG5-0005	VOC	30 TAC Chapter 115, Loading and Unloading of VOC	§ 115.217(a)(1) § 115.212(a)(2) § 115.214(a)(1)(B) § 115.214(a)(1)(D) § 115.214(a)(1)(D)(i)	Vapor pressure (at land-based operations). All land-based loading and unloading of VOC with a true vapor pressure less than 0.5 psia is exempt from the requirements of this division, except as specified.	§ 115.214(a)(1)(A) § 115.214(a)(1)(A)(i) § 115.215 § 115.215(4)	§ 115.216 § 115.216(2) § 115.216(3)(B)	None
GRPJFo2	EU	60XX-0001	TOC	40 CFR Part 60, Subpart XX	§ 60.502(a) § 60.502(c) § 60.502(d) § 60.502(g) § 60.502(h) § 60.502(i)	Each bulk gasoline terminal facility shall be equipped with a vapor collection system designed to collect the total organic compounds vapors displaced from tank trucks during product loading.	§ 60.502(j) § 60.503(a) § 60.503(b) § 60.503(c)(1) § 60.503(c)(3) § 60.503(c)(4) § 60.503(c)(5)(i) § 60.503(c)(6) § 60.503(c)(7)	§ 60.502(j) § 60.503(c)(4) § 60.503(d)(2) [G]§ 60.505(c) [G]§ 60.505(e) § 60.505(f)	[G]§ 60.505(e)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
							§ 60.503(d) § 60.503(d)(1) § 60.503(d)(2) ** See CAM Summary		
GRPJFo2	EU	63BBBBB-1	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11088(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart BBBBBB
GRPJFo4	EU	R5112-01	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPJFo4	EU	R5112-02	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
GRPJFo4	EU	R5112-03	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.112(e)(1) § 115.112(e)(2) § 115.112(e)(2)(A) § 115.112(e)(2)(B) § 115.112(e)(2)(C) § 115.112(e)(2)(D) § 115.112(e)(2)(F)	No person shall place, store, or hold VOC in any storage tank unless the storage tank is capable of maintaining working pressure sufficient at all times to prevent any	§ 115.114(a)(1) § 115.114(a)(1)(A) [G]§ 115.117	§ 115.118(a)(3) § 115.118(a)(5) § 115.118(a)(6)(C) § 115.118(a)(7)	§ 115.114(a)(1)(B) § 115.118(a)(3)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
					[G]§ 115.112(e)(2)(I) § 115.114(a)(1)(A)	vapor or gas loss to the atmosphere or is in compliance with the control requirements specified in Table 1 of this paragraph for VOC other than crude oil and condensate or Table 2 of subsection (a)(1) of this paragraph for crude oil and condensate.			
GRPJFo4	EU	60Kb-2	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs for which construction/reconstruction/modification began after 7/23/84.	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)
GRPJFo4	EU	60Kb-3	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) § 60.116b(e)(2)(i)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRPJFo4	EU	60Kb-5	VOC	40 CFR Part 60, Subpart Kb	§ 60.110b(a)	Except for §60.110b(b), this subpart applies to vessels with a capacity greater than or equal to 75 cubic meters (19,800 gal) used to store VOLs	§ 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(d) § 60.116b(e) § 60.116b(e)(1)	§ 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.116b(d)

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						for which construction/reconstruction/modification began after 7/23/84.	[G]§ 60.116b(e)(3)		
GRPJFo4	EU	60Kb-6	VOC	40 CFR Part 60, Subpart Kb	§ 60.112b(a)(1) § 60.112b(a)(1)(i) § 60.112b(a)(1)(ii)(C) § 60.112b(a)(1)(iii) § 60.112b(a)(1)(iv) § 60.112b(a)(1)(ix) § 60.112b(a)(1)(v) § 60.112b(a)(1)(vi) § 60.112b(a)(1)(vii) § 60.112b(a)(1)(viii)	Storage vessels specified in §60.112b(a) and equipped with a fixed roof in combination with an internal floating roof shall meet the specifications listed in §60.112b(a)(1)(i)-(ix).	§ 60.113b(a)(1) § 60.113b(a)(2) § 60.113b(a)(4) § 60.113b(a)(5) § 60.116b(a) § 60.116b(b) § 60.116b(c) § 60.116b(e) § 60.116b(e)(1) [G]§ 60.116b(e)(3)	§ 60.115b § 60.115b(a)(2) § 60.116b(a) § 60.116b(b) § 60.116b(c)	§ 60.113b(a)(2) § 60.113b(a)(5) § 60.115b § 60.115b(a)(1) § 60.115b(a)(3)
GRPJFo4	EU	63BBBBBB-1	112(B) HAPS	40 CFR Part 63, Subpart BBBBBB	§ 63.11087(a) The permit holder shall comply with the applicable limitation, standard and/or equipment specification requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable monitoring and testing requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable recordkeeping requirements of 40 CFR Part 63, Subpart BBBBBB	The permit holder shall comply with the applicable reporting requirements of 40 CFR Part 63, Subpart BBBBBB
T30-4	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(6)(A) § 115.118(a)(7)	None
T80-4	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).			
TK71001	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK71002	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK71003	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true vapor pressure less than 1.5 psia is exempt from the requirements of this division.	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None
TK71004	EU	R5112-1	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.111(a)(1)	Except as provided in § 115.118, a storage tank storing VOC with a true	[G]§ 115.117	§ 115.118(a)(1) § 115.118(a)(5) § 115.118(a)(7)	None

Applicable Requirements Summary

Unit Group Process ID No.	Unit Group Process Type	SOP Index No.	Pollutant	State Rule or Federal Regulation Name	Emission Limitation, Standard or Equipment Specification Citation	Textual Description (See Special Term and Condition 1.B.)	Monitoring And Testing Requirements	Recordkeeping Requirements (30 TAC § 122.144)	Reporting Requirements (30 TAC § 122.145)
						vapor pressure less than 1.5 psia is exempt from the requirements of this division.			
TR SUMP-1	EU	TAC115-SUMP	VOC	30 TAC Chapter 115, Storage of VOCs	§ 115.117(a)(1)	Except as provided in §115.116 of this title (relating to Monitoring and Recordkeeping Requirements), any volatile organic compound (VOC) with a true vapor pressure less than 1.5 pounds per square inch absolute (psia) (10.3 kPa) at storage conditions is exempt from the requirements of this division (relating to the Storage of Volatile Organic Compounds).	§ 115.116(a)(5)	§ 115.116(a)(5) § 115.116(c)(1)	None

Additional Monitoring Requirements

Compliance Assurance Monitoring Summary 32

CAM Summary

Unit/Group/Process Information	
ID No.: GRPJFo2	
Control Device ID No.: VCU 1A	Control Device Type: Vapor Combustor
Control Device ID No.: VCU 1B	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: REG5-0001
Pollutant: VOC	Main Standard: § 115.211(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 955 Degrees F (VCU 1A) Minimum combustion temperature = 996 Degrees F (VCU 1B)	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPJFo2	
Control Device ID No.: VCU 1A	Control Device Type: Vapor Combustor
Control Device ID No.: VCU 1B	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 30 TAC Chapter 115, Loading and Unloading of VOC	SOP Index No.: REG5-0003
Pollutant: VOC	Main Standard: § 115.211(1)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 955 Degrees F (VCU 1A) Minimum combustion temperature = 996 Degrees F (VCU 1B)	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

CAM Summary

Unit/Group/Process Information	
ID No.: GRPJFo2	
Control Device ID No.: VCU 1A	Control Device Type: Vapor Combustor
Control Device ID No.: VCU 1B	Control Device Type: Vapor Combustor
Applicable Regulatory Requirement	
Name: 40 CFR Part 60, Subpart XX	SOP Index No.: 60XX-0001
Pollutant: TOC	Main Standard: § 60.502(a)
Monitoring Information	
Indicator: Combustion Temperature / Exhaust Gas Temperature	
Minimum Frequency: four times per hour	
Averaging Period: one hour	
Deviation Limit: Minimum combustion temperature = 955 Degrees F (VCU 1A) Minimum combustion temperature = 996 Degrees F (VCU 1B)	
<p>CAM Text: The monitoring device should be installed in the combustion chamber or immediately downstream of the combustion chamber. Each monitoring device shall be calibrated at a frequency in accordance with the manufacturer's specifications, other written procedures that provide an adequate assurance that the device is calibrated accurately, or at least annually, whichever is more frequent, and shall be accurate to within one of the following:</p> <ul style="list-style-type: none"> ± 2% of reading; or ± 2.5 degrees Celsius. 	

New Source Review Authorization References

New Source Review Authorization References 36

New Source Review Authorization References by Emission Unit..... 37

New Source Review Authorization References

The New Source Review authorizations listed in the table below are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 78902	Issuance Date: 05/19/2006
Authorization No.: 8886	Issuance Date: 10/15/2010
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.261	Version No./Date: 12/24/1998
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.452	Version No./Date: 03/14/1997
Number: 106.454	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 03/14/1997
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 09/04/2000
Number: 106.511	Version No./Date: 09/04/2000
Number: 51	Version No./Date: 09/23/1982
Number: 86	Version No./Date: 09/23/1982

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
A-1	10,000 GAL GASOLINE ADDITIVE TANK	8886
A-2	4,000 GAL DIESEL ADDITIVE TANK	8886
A-3	2000 GAL ADDITIVE TANK	106.473/03/14/1997
A-4	HFR DIESEL ADDITIVE STORAGE TANK	8886
BAY 1	TRUCK LOADING BAY	8886
BAY 2	TRUCK LOADING BAY	8886
BAY 3	TRUCK LOADING BAY	8886
BAY 4	TRUCK LOADING BAY	8886
BAY 5	TRUCK LOADING BAY	8886
BAY 6	LOADING BAY 6	8886
BAY 7	LOADING BAY 7	8886
BAY 8	LOADING BAY 8	8886
BAY 9	LOADING BAY 9	8886
FUGITIVES	FUGITIVE COMPONENTS	8886
T10-13	WASTE WATER STORAGE TANK	8886
T30-4	FIXED ROOF TANK	106.261/11/01/2003, 106.472/09/04/2000
T35-1	TANK 35-1	8886
T35-2	TANK 35-2	8886

New Source Review Authorization References by Emissions Unit

The following is a list of New Source Review (NSR) authorizations for emission units listed elsewhere in this operating permit. The NSR authorizations are applicable requirements under 30 TAC Chapter 122 and enforceable under this operating permit.

Unit/Group/Process ID No.	Emission Unit Name/Description	New Source Review Authorization
T35-3	TANK 35-3	8886
T35-4	FIXED ROOF TANK	106.261/11/01/2003, 106.472/09/04/2000
T50-4	INTERNAL FLOATING ROOF STORAGE TANK	8886
T80-1	TANK 80-1	8886
T80-2	TANK 80-2	8886
T80-3	TANK 80-3	8886
T80-4	TANK 80-4	8886
T80-5	IFR TANK	106.261/11/01/2003, 106.263/11/01/2001, 106.478/09/04/2000
TK71001	VFR GASOLINE ADDITIVE STORAGE TANK	8886
TK71002	VFR GASOLINE ADDITIVE STORAGE TANK	8886
TK71003	HFR LUBRICITY ADDITIVE STORAGE TANK	8886
TK71004	HFR DIESEL ADDITIVE STORAGE TANK	8886
TR SUMP-1	WASTEWATER SUMP	8886

Appendix A

Acronym List	40
--------------------	----

Acronym List

The following abbreviations or acronyms may be used in this permit:

ACFM	actual cubic feet per minute
AMOC	alternate means of control
ARP	Acid Rain Program
ASTM	American Society of Testing and Materials
B/PA	Beaumont/Port Arthur (nonattainment area)
CAM	Compliance Assurance Monitoring
CD	control device
COMS	continuous opacity monitoring system
CVS	closed-vent system
D/FW	Dallas/Fort Worth (nonattainment area)
DR	Designated Representative
ELP	El Paso (nonattainment area)
EP	emission point
EPA	U.S. Environmental Protection Agency
EU	emission unit
FCAA Amendments	Federal Clean Air Act Amendments
FOP	federal operating permit
GF	grandfathered
gr/100 scf	grains per 100 standard cubic feet
HAP	hazardous air pollutant
H/G/B	Houston/Galveston/Brazoria (nonattainment area)
H ₂ S	hydrogen sulfide
ID No.	identification number
lb/hr	pound(s) per hour
MMBtu/hr	Million British thermal units per hour
MRRT	monitoring, recordkeeping, reporting, and testing
NA	nonattainment
N/A	not applicable
NADB	National Allowance Data Base
NO _x	nitrogen oxides
NSPS	New Source Performance Standard (40 CFR Part 60)
NSR	New Source Review
ORIS	Office of Regulatory Information Systems
Pb	lead
PBR	Permit By Rule
PM	particulate matter
ppmv	parts per million by volume
PSD	prevention of significant deterioration
RO	Responsible Official
SO ₂	sulfur dioxide
TCEQ	Texas Commission on Environmental Quality
TSP	total suspended particulate
TVP	true vapor pressure
U.S.C.	United States Code
VOC	volatile organic compound